

## Heating Wrap LIGHT

Frost protection especially for pipes and drains at construction sites. The structure of the product is a self-limiting heating cable with an earthing screen of aluminium foil – effect 17 W/m at 10 °C – which is mounted in an insulated wrap that can be wrapped around the pipe and closed with velcro. The heating wrap can be used on pipes up to 50 mm. For larger elements and pipe dimensions, two or more wraps can be used, which are simply held together using Velcro. This construction provides a quickly and efficiently mounting at the construction site that is easy to dismantle and can be re-used.

The heating wrap can be delivered with a DK, Schuko or three-poled IEC 309 plug.

The minimum installation temperature is -30 °C.

Its use includes temporary installations for on-site office trailers, mobile bathrooms, and similar facilities.

Product range from 5 m - 25 m and comes in 5 sizes.



### Technical Data



Voltage	230 V ~ 50 Hz
Power supply line	1.5 m
Degree of protection	IP44 (plug) - IP57 (cable)
Effect	17 W/m
Material	PE-foil 0.15 mm
Initial fuse	10 A
Athorisation	CE
Guarantee cable	3 years

## Heating Wrap LIGHT Schuko plug

Item	Description	Plug	Effect Watt/10 °C	Power
50863105	Heating wrap LIGHT 5 m	Schuko	85 W	0.4 A
50863105	Heating wrap LIGHT 10 m	Schuko	170 W	0.7 A
50863105	Heating wrap LIGHT 15 m	Schuko	255 W	1.1 A
50863105	Heating wrap LIGHT 20 m	Schuko	340 W	1.6 A
50863105	Heating wrap LIGHT 25 m	Schuko	425 W	1.8 A

## Heating Wrap LIGHT IEC309 plug

Item	Description	Plug	Effect Watt/10 °C	Power
50863305	Heating wrap LIGHT 5 m	IEC309	85 W	0.4 A
50863305	Heating wrap LIGHT 10 m	IEC309	170 W	0.7 A
50863305	Heating wrap LIGHT 15 m	IEC309	255 W	1.1 A
50863305	Heating wrap LIGHT 20 m	IEC309	340 W	1.6 A
50863305	Heating wrap LIGHT 25 m	IEC309	425 W	1.8 A